

## **∆ightstec®** LT-5050MIC144R-W5 **Specification**

#### I. Product Description

- Every LED works as an individual pixel, it can achieve effects of Full Color Water Running, Chasing and Scanning, which thanks to its high brightness.
  - This LED strip could only be linked up to 2 meters, more than 2 meters is strictly prohibited.
- The diameter of the power wires should be based on the actual maximum current, power, and its cabling length (no more than 2 meters), and the voltage of transmission line.
  - Widely applied to hotel, KTV entertainment place for interior decorative lighting, etc.

#### II. Physical parameters

Working Voltage: DC5V

LED resource: WS2812B LED(5050 SMD RGB LED with built-in WS2811S IC)

**LED Type**: SMD5050 RGB LED Quantity: 144LEDs/Meter

Working Current: 0.06A/Cut; 8.64A/Meter

Width: 12mm Length: 2 Meters per Reel Max. Power: 43.2Watt/meter Viewing angle: ≥140°C FPCB Color: White/Black Circuit board: Double FPCB

Package: Anti-static plastic bag

Weight: 120g(Silicone Glue) 60g(Bare board) 1000g(Silicone Tube)

IP Grade: IP20/IP55/IP65

Working Temperature: -40°C ~ 60°C Storage temperature: -50°C ~ 80°C

Lifespan: 50000 Hours

Terminal connectors: 3pin Connector

#### **III. Glowing Effect**



# LT-5050MIC144R-W5 Specification

### IV. Distribution wiring diagram

