

I. Product Description

- Every LED works as an individual pixel, it can achieve effects of Full Color Water Running, Chasing and Scanning, which thanks to its high brightness.
- This LED strip could only be linked up to 5 meters, more than 5 meters is strictly prohibited.
- The diameter of the power wires should be based on the actual maximum current, power, and its cabling length (no more than 5 meters), and the voltage of transmission line.
- Widely applied to hotel, KTV entertainment place for interior decorative lighting, etc.

II. Physical parameters

Working Voltage: DC5V

LED resource: WS2812B LED(5050 SMD RGB LED with built-in WS2811S IC)

LED Type: SMD5050 RGB

LED Quantity: 60LEDs/Meter

Working Current: 0.06A/Cut; 3.6A/Meter

Width: 10mm

Length: 4 Meters per Reel

Max. Power: 18Watt/meter

Viewing Angle: $\geq 140^{\circ}$

Circuit Board: Double FPCB

FPCB Color: White/Black

Package: Anti-static plastic bag

Weight: 240g(Silicone Glue) 100g(Bare board) 200g(Silicone Tube)

IP Grade: IP20/IP55/IP65

Working Temperature: $-40^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Storage Temperature: $-50^{\circ}\text{C} \sim 80^{\circ}\text{C}$

Lifespan: 50000 Hours

Terminal connectors: 3pin Connector

III. Glowing Effect



LT-5050MIC60R-W5 Specification

IV. Distribution wiring diagram

